



I *Sense® HS48M



The IFOS I*Sense® HS48M offers a state of the art ultra-high-speed integrated solution for monitoring up to 16 Fiber Bragg Grating (FBG) sensors.

Key features and benefits of the IFOS I*Sense® are:

- Directly measures temperature, static and dynamic strain
- Can measure vibration, acoustics and acoustic emission
- Multiple sensors multiplexed on a single fiber
- High speed of up to 3 MHz for every FBG per fiber
- High resolution, accuracy, and dynamic range
- Automatic calibration
- Scalable with multiple fiber connection capabilities
- Remote monitoring system for up to 100 km
- Solid state, no moving parts
- Compact, lightweight, low power consumption
- Operates in harsh and demanding environments
- Long life and high reliability
- Integrated intelligent monitoring system
- Customizable decision aid algorithms and displays
- Fiber or wireless backhaul transmission capability

The I*Sense® provides simultaneous data display and storage for all its channels with every FBG seeing the full bandwidth, offering high precision, remote monitoring, long life, large dynamic range, and high measurement range with multiple optical bands available for expansion. Different sensing elements can be deployed on a single optical fiber enabling a mix of strain, temperature and derivative measurements for e.g. displacement, tilt, pressure, chemical and biochemical measurements, to best meet varying customer needs at a series of discrete locations. Customized sensors are available upon request.

I*Sense® HS48M Product Specs*

Number of Fibers	4 (larger numbers optional with additional external switch module and firmware key)
Number of sensors per fiber	4 (16 with external switch option)
Strain Range	± 1330 µstrain (C band; 12 sensors per fiber)
Detection Speed	500kHz, 1MHz, 2 MHz or 3 MHz options
Resolution	0.1 pm
Absolute Accuracy	+/- 2 pm
Dynamic Range	50 dB
Maximum Reach	100 km
Optical Connectors	FC or E2000 APC
Operating Temp. Range	0-55° C (-10-70° C optional)
Optical Power	5 to 14 dBm
Power Supply Voltage	85-240 V
Power Consumption	50 W
Dimensions (WxDxH)	430 x 460 x 178 mm Rack mount 4U
Weight	15 kg
Lifetime	>25 years
Wavelength Range	C (Multiple bands optional)
Interface	Integrated PC
Software	Windows 7, XP, C++, LabVIEW, Matlab GUI / Library

**These specifications are indicative and may change without notice*